

**Description**

Diameter: 1/4", slotted, steel comp

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AJ325
Minimum Qty (MOQ):	10
NSN:	5325-00-282-8138
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AJ3-25 Specifications

<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Diameter:</b>	0.312 Inches Nominal
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Material Accommodated Thickness:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Shank Neck Length:</b>	0.065 Inches Minimum And 0.085 Inches Maximum
<b>Stud Shank Major Diameter:</b>	0.182 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Steel Comp 1315 Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/AJ3-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.