

## **P/N AN10-13A**

### **Description**

Fastener Length: 1-33/64", Thread: 5/8-18, Thread Length: 61/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN1013A
Minimum Qty (MOQ): 10 EA

NSN: 5306-00-180-0093

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN10-13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.954 Inches Minimum
Fastener Length:	1.516 Inches Nominal
Head Style:	Hexagon
Head Height:	0.328 Inches Minimum And 0.360 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	0.562 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

# **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AN10-13A">https://military-fasteners.com/bolts/machine+bolts/AN10-13A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.