



Military-Fasteners.com

P/N AN10-35

## Description

Fastener Length: 3-51/64", Thread: 5/8-18, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN1035
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-151-1455
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN10-35 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.922 Inches Minimum And 1.000 Inches Maximum
<b>Fastener Length:</b>	3.750 Inches Minimum And 3.797 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.328 Inches Minimum And 0.360 Inches Maximum
<b>Width Between Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Grip Length:</b>	2.797 Inches Minimum And 2.844 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	3.531 Inches Minimum First Hole And 3.562 Inches Maximum First Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN10-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.