

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN101120 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-282-0908 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN101120 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.615 Inches Minimum And 0.695 Inches Maximum |
| Fastener Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.690 Inches Minimum And 0.750 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Material: | Steel Comp 8740 Overall |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN101120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.