

**Description**

Fastener Length: 5/8", Thread: 1/4-24, Thread Length: 39/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | AN101206                                  |
| Minimum Qty (MOQ):      | 20                                        |
| NSN:                    | 5306-00-285-5516                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN101206 Specifications

|                                                       |                                                                     |
|-------------------------------------------------------|---------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                  |
| <b>Thread Direction:</b>                              | Right-hand                                                          |
| <b>Thread Length:</b>                                 | 0.532 Inches Minimum And 0.615 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.615 Inches Minimum And 0.635 Inches Maximum                       |
| <b>Head Style:</b>                                    | Hexagon                                                             |
| <b>Head Height:</b>                                   | 0.178 Inches Minimum And 0.198 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.502 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches                                                        |
| <b>Features Provided:</b>                             | Finished Head                                                       |
| <b>Thread Quantity Per Inch:</b>                      | 24                                                                  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                            |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Material:</b>                                      | Steel Comp 8740 Overall                                             |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall                                                     |
| <b>Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response Overall                 |
| <b>Thread Series Designator:</b>                      | Unf                                                                 |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN101206> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.