

Description

Fastener Length: 1-3/16", Thread: 3/8-24, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN101313
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-283-0454
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN101313 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	1.188 Inches Nominal
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.438 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this hex head bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN101313> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.