

**Description**

Fastener Length: 1-5/16", Thread: 3/8-24, Thread Length: 13/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN101315                                  |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-00-282-9865                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN101315 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.740 Inches Minimum And 0.820 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 1.302 Inches Minimum And 1.322 Inches Maximum                       |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.209 Inches Minimum And 0.229 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.553 Inches Minimum And 0.564 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 0.502 Inches Minimum And 0.562 Inches Maximum                       |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Material:</b>                                      | Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response Overall                 |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN101315> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.