

## P/N AN103815

### **Description**

Fastener Length: 1", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 51/64", AN1038 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN103815

Minimum Qty (MOQ): 10

NSN: 5306-00-584-5384

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# **P/N AN103815 Specifications**

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.750 Inches Minimum And 0.810 Inches Maximum                       |
| Fastener Length:                               | 1.062 Inches Nominal  |
| Head Style:                                    | Hexagon   |
| Head Height:                                   | 0.240 Inches Minimum And 0.260 Inches Maximum                       |
| Width Between Flats:                           | 0.430 Inches Minimum And 0.439 Inches Maximum                       |
| Hole Diameter:                                 | 0.070 Inches Nominal  |
| Nominal Thread Diameter:                       | 0.250 Inches  |
| Grip Length:                                   | 0.252 Inches Minimum And 0.312 Inches Maximum                       |
| Hole Quantity:                                 | 6   |
| Hole Type:                                     | Drilled   |
| Features Provided:                             | Finished Head   |
| Thread Quantity Per Inch:                      | 28  |
| Minimum Tensile Strength:                      | 125000 Pounds Per Square Inch                                       |
| Hardness Rating:                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Hole Configuration Style:                      | Hexagon Longitudinal Hole   |
| Surface Finish:                                | 32.0 Microinches Threads  |
| Surface Finish:                                | 63.0 Microinches Bearing Surface Of Head                            |
| Surface Finish:                                | 63.0 Microinches Grip   |
| Material:                                      | Steel Comp 8740 Overall   |
| Material Document And Classification:          | Ams 6322 Assn Std Single Material Response Overall                  |
| Surface Treatment:                             | Cadmium Overall   |
| Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response Overall                 |
| Thread Series Designator:                      | Unf   |
|  |   |

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AN103815">https://military-fasteners.com/bolts/machine+bolts/AN103815</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.