

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN106406 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-281-2588 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN106406 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.303 Inches Minimum And 0.323 Inches Maximum |
| Fastener Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Steel Comp 302 Overall |
| Material Document And Classification: | Ams 5637 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN106406> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.