

**Description**

Fastener Length: 2-1/64", Hole Diameter: 5/64", Thread: 3/8-24, Thread Length: 1-1/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN106728                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-514-9250                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN106728 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 1.000 Inches Minimum                               |
| <b>Fastener Length:</b>                      | 2.000 Inches Nominal                               |
| <b>Head Style:</b>                           | Hexagon  |
| <b>Head Height:</b>                          | 0.219 Inches Nominal                               |
| <b>Width Between Flats:</b>                  | 0.553 Inches Minimum And 0.564 Inches Maximum      |
| <b>Hole Diameter:</b>                        | 0.070 Inches Nominal                               |
| <b>Nominal Thread Diameter:</b>              | 0.375 Inches                                       |
| <b>Grip Length:</b>                          | 1.000 Inches Nominal                               |
| <b>Hole Quantity:</b>                        | 1  |
| <b>Hole Type:</b>                            | Drilled  |
| <b>Features Provided:</b>                    | Finished Head                                      |
| <b>Thread Quantity Per Inch:</b>             | 24   |
| <b>Hole Configuration Style:</b>             | Hexagon Flats                                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                           |
| <b>Surface Finish:</b>                       | 63.0 Microinches Bearing Surface Of Head           |
| <b>Surface Finish:</b>                       | 63.0 Microinches Grip                              |
| <b>Material:</b>                             | Steel Corrosion Resisting Overall                  |
| <b>Material Document And Classification:</b> | Ams 7472 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN106728> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.