

Description

Fastener Length: 11/16", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN107409 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-514-9227 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN107409 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.617 Inches Minimum |
| Fastener Length: | 0.688 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.070 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Steel Comp 4037 Overall |
| Material Document And Classification: | Ams 6300 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN107409> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.