



Military-Fasteners.com

P/N AN10C21

Description

Fastener Length: 2-17/64", Thread: 5/8-18, Thread Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN10C21
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-582-6953
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN10C21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.954 Inches Minimum
Fastener Length:	2.266 Inches Nominal
Head Style:	Hexagon
Head Height:	0.328 Inches Minimum And 0.360 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Nominal First Hole
Nominal Thread Diameter:	0.625 Inches
Grip Length:	1.312 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.046 Inches Nominal First Hole
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-770 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN10C21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.