

**Description**

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN115807                                  |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-271-7746                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN115807 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.323 Inches Minimum And 0.385 Inches Maximum       |
| <b>Fastener Length:</b>                                     | 0.365 Inches Minimum And 0.385 Inches Maximum       |
| <b>Head Style:</b>  | Flat Chamfer  |
| <b>Head Diameter:</b>                                       | 0.292 Inches Minimum And 0.313 Inches Maximum       |
| <b>Head Height:</b>   | 0.209 Inches Minimum And 0.229 Inches Maximum       |
| <b>Hole Diameter:</b>                                       | 0.042 Inches Minimum And 0.052 Inches Maximum       |
| <b>Internal Drive Style:</b>                                | Slot  |
| <b>Nominal Thread Diameter:</b>                             | 0.190 Inches  |
| <b>Hole Quantity:</b>                                       | 2   |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch                       |
| <b>Hardness Rating:</b>                                     | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| <b>Screw Material:</b>                                      | Steel Comp 8740                                     |
| <b>Screw Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response          |
| <b>Screw Surface Treatment:</b>                             | Cadmium   |
| <b>Screw Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response         |
| <b>Head Hole Configuration Style:</b>                       | Round   |
| <b>Thread Series Designator:</b>                            | Unf   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN115807> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.