

## **P/N AN115832**

## **Description**

Fastener Length: 2-3/8", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN115832
Minimum Qty (MOQ):	1
NSN:	5305-00-017-6093
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN115832 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.553 Inches Minimum And 0.695 Inches Maximum
Fastener Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.209 Inches Minimum And 0.229 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	2
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8740
Screw Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN115832">https://military-fasteners.com/screws/machine+screws/AN115832</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.