

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN116905
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-281-8540
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN116905 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.398 Inches Minimum And 0.448 Inches Maximum
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.166 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.069 Inches Minimum And 0.079 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	70000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum And 100.0 Rockwell B Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Ams 5061 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN116905> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.