

Description

Fastener Length: 1/2", Hole Diameter: 1/32", Thread: 6-32, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN116966 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-271-8058 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN116966 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.428 Inches Minimum And 0.490 Inches Maximum |
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.208 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.144 Inches Minimum And 0.154 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.138 Inches |
| Hole Quantity: | 2 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 70000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum And 100.0 Rockwell B Maximum |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Ams 5061 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN116966> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.