

**Description**

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 6-32, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN116968
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-637-6641
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN116968 Specifications

<b>Thread Class:</b>	1a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.553 Inches Minimum And 0.615 Inches Maximum
<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.108 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.144 Inches Minimum And 0.154 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Nominal
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Hole Quantity:</b>	2
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	70000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum And 100.0 Rockwell B Maximum
<b>Screw Material:</b>	Steel
<b>Screw Material Document And Classification:</b>	Ams 5061 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN116968> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.