

Description

Fastener Length: 1/2", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 31/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN117046
Minimum Qty (MOQ):	5
NSN:	5305-00-637-7439
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN117046 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.428 Inches Minimum And 0.490 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.160 Inches Minimum And 0.171 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	2
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	70000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum And 100.0 Rockwell B Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Ams 5061 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN117046> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.