

**Description**

AN121603 Straight Headed Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN121603
Minimum Qty (MOQ):	2
NSN:	5315-00-820-9066
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N AN121603 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Chamfer Length:</b>	0.037 Inches Minimum And 0.057 Inches Maximum
<b>Diameter:</b>	0.122 Inches Minimum And 0.124 Inches Maximum
<b>Under Head Length:</b>	0.459 Inches Minimum And 0.479 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.065 Inches Minimum And 0.072 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.081 Inches Minimum And 0.101 Inches Maximum
<b>Features Provided:</b>	Casehardened
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Pin Chamfer Angle:</b>	10.0 Degrees Minimum And 20.0 Degrees Maximum
<b>Pin Head Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Surface Finish:</b>	63.0 Microinches Head Bearing Surface
<b>Height:</b>	0.037 Inches Minimum And 0.057 Inches Maximum
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response Overall
<b>Style Designator:</b>	Straight

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/AN121603> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.