

Description

AN121603 Straight Headed Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN121603
Minimum Qty (MOQ):	2
NSN:	5315-00-820-9066
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N AN121603 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.037 Inches Minimum And 0.057 Inches Maximum
Diameter:	0.122 Inches Minimum And 0.124 Inches Maximum
Under Head Length:	0.459 Inches Minimum And 0.479 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.065 Inches Minimum And 0.072 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.081 Inches Minimum And 0.101 Inches Maximum
Features Provided:	Casehardened
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	10.0 Degrees Minimum And 20.0 Degrees Maximum
Pin Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Surface Finish:	63.0 Microinches Head Bearing Surface
Height:	0.037 Inches Minimum And 0.057 Inches Maximum
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/AN121603> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.