

**Description**

Fastener Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123154
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-073-0214
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123154 Specifications

<b>Fastener Length:</b>	0.312 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.061 Inches Minimum And 0.063 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Hardness Rating:</b>	165.0 Vickers Or Firth Diamond Pyramid Maximum Overall
<b>Heat Treatment:</b>	Solution Heat Treated Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 7229 Assn Std Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123154> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.