

Description

Fastener Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN123156                                    |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5320-00-551-7618                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

# P/N AN123156 Specifications

|                                       |  |
|---------------------------------------|--|
| Fastener Length:                      | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| Head Style:                           | Universal  |
| Head Height:                          | 0.027 Inches Minimum And 0.037 Inches Maximum      |
| Shank Diameter:                       | 0.061 Inches Minimum And 0.063 Inches Maximum      |
| Shank Style:                          | Straight   |
| Head Major Diameter:                  | 0.119 Inches Minimum And 0.131 Inches Maximum      |
| Grip Length:                          | 0.316 Inches Minimum And 0.336 Inches Maximum      |
| Material:                             | Steel Comp 347 Overall                             |
| Material Document And Classification: | Ams 7229 Assn Std Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123156> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.