

Description

Fastener Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------------------|
| SKU / Model: | AN123157 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5320-00-641-9475 |
| Schedule B: | 7318.16.0060 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123157 Specifications

| | |
|----------------------------------------------|----------------------------------------------------|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.027 Inches Minimum And 0.037 Inches Maximum |
| Shank Diameter: | 0.061 Inches Minimum And 0.063 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.119 Inches Minimum And 0.131 Inches Maximum |
| Grip Length: | 0.378 Inches Minimum And 0.398 Inches Maximum |
| Material: | Steel Comp 347 Overall |
| Material Document And Classification: | Ams 7229 Assn Std Single Material Response Overall |

How to Order

Order this rivsolid from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123157> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.