

## P/N AN123168

### **Description**

Fastener Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN123168

Minimum Qty (MOQ): 100


NSN: 5320-00-279-1289

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# **P/N AN123168 Specifications**

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.179 Inches Minimum And 0.197 Inches Maximum
Grip Length:	0.009 Inches Minimum And 0.029 Inches Maximum
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ams 7229 Assn Std Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123168">https://military-fasteners.com/rivets/solid+rivets/AN123168</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.