

# **P/N AN123187**

## **Description**

Fastener Length: 3/8, roughly 550 pieces per pound

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN123187

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-270-2746

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123187 Specifications**

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.140 Inches Minimum And 0.160 Inches Maximum
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ms 7229 Assn Std Single Material Response Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123187">https://military-fasteners.com/rivets/solid+rivets/AN123187</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123187">https://military-fasteners.com/rivets/solid+rivets/AN123187</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123187">https://military-fasteners.com/rivets/solid+rivets/AN123187</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123187">https://military-fasteners.com/rivets/solid+rivets/AN123187</a> and selecting the quantity you want then click "add to cart".