

Description

Fastener Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123248
Minimum Qty (MOQ):	100
NSN:	5320-00-143-5917
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123248 Specifications

Fastener Length:	0.271 Inches Minimum And 0.291 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.066 Inches Nominal
Heat Treatment:	As Fabricated Overall
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ams 7229 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123248> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.