

# P/N AN123291

### **Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN123291
Minimum Qty (MOQ):	50
NSN:	5320-00-143-5915
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123291 Specifications**

Fastener Length:	0.334 Inches Minimum And 0.354 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.154 Inches Minimum And 0.157 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grip Length:	0.062 Inches Nominal
Heat Treatment:	As Fabricated Overall
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ams 7229 Assn Std Single Material Response Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123291">https://military-fasteners.com/rivets/solid+rivets/AN123291</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.