

Description

Fastener Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN123293
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-288-6630
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123293 Specifications

Fastener Length:	0.459 Inches Minimum And 0.479 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.154 Inches Minimum And 0.157 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Hardness Rating:	165.0 Vickers Or Firth Diamond Pyramid Maximum Overall
Heat Treatment:	Solution Heat Treated Overall
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ams 7229 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123293> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.