

## **P/N AN123308**

### **Description**

Fastener Length: 5/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN123308

Minimum Qty (MOQ): 130 EA

NSN: 5320-00-407-5659

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN123308 Specifications

Fastener Length:	0.146 Inches Minimum And 0.166 Inches Maximum
Head Style:	Universal
Head Height:	0.027 Inches Minimum And 0.037 Inches Maximum
Shank Diameter:	0.061 Inches Minimum And 0.063 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.119 Inches Minimum And 0.131 Inches Maximum
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

# **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123308">https://military-fasteners.com/rivets/solid+rivets/AN123308</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="here">here</a> to complete your order.