

### **P/N AN123314**

### **Description**

Fastener Length: 7/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model: AN123314

Minimum Qty (MOQ): 100 EA

NSN: 5320-00-935-1242

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123314 Specifications**

Fastener Length:	0.219 Inches Nominal
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.179 Inches Minimum And 0.197 Inches Maximum
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy Overall

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123314">https://military-fasteners.com/rivets/solid+rivets/AN123314</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123314">https://military-fasteners.com/rivets/solid+rivets/AN123314</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123314">https://military-fasteners.com/rivets/solid+rivets/AN123314</a> and selecting the quantity you want then click "add to cart".