

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | AN123316 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-891-3360 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123316 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.344 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.179 Inches Minimum And 0.197 Inches Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Nickel Alloy 600 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123316> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.