

Description

Fastener Length: 13/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN123317
Minimum Qty (MOQ):	100
NSN:	5320-01-171-8135
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N AN123317 Specifications

Fastener Length:	0.406 Inches Nominal
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.179 Inches Minimum And 0.197 Inches Maximum
Hardness Rating:	151.0 Vickers Or Firth Diamond Pyramid Maximum Overall
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123317> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.