

**Description**

Fastener Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123322
Minimum Qty (MOQ):	65 EA
NSN:	5320-00-550-4055
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N AN123322 Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.095 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.179 Inches Minimum And 0.197 Inches Maximum
<b>Grip Length:</b>	0.259 Inches Minimum And 0.279 Inches Maximum
<b>Material:</b>	Nickel Alloy 600 Overall
<b>Material Document And Classification:</b>	Ams 7232 Assn Std Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123322> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.