

**Description**

Fastener Length: 7/16", universal head, roughly 450 pieces per pound, AN12333 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN123338                                    |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-00-270-2760                            |
| Schedule B:             | 7508.90.5000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N AN123338 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| <b>Head Style:</b>                           | Universal  |
| <b>Head Height:</b>                          | 0.054 Inches Minimum And 0.064 Inches Maximum      |
| <b>Shank Diameter:</b>                       | 0.123 Inches Minimum And 0.126 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight   |
| <b>Head Major Diameter:</b>                  | 0.238 Inches Minimum And 0.262 Inches Maximum      |
| <b>Grip Length:</b>                          | 0.203 Inches Minimum And 0.223 Inches Maximum      |
| <b>Material:</b>                             | Nickel Alloy 600 Overall                           |
| <b>Material Document And Classification:</b> | Ams 7232 Assn Std Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123338> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.