

P/N AN123338

Description

Fastener Length: 7/16", universal head, roughly 450 pieces per pound, AN12333 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | AN123338 |
|-------------------------|---|
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-270-2760 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



^{*} See page 2 for technical characteristics

P/N AN123338 Specifications

| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
|---------------------------------------|--|
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.123 Inches Minimum And 0.126 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Grip Length: | 0.203 Inches Minimum And 0.223 Inches Maximum |
| Material: | Nickel Alloy 600 Overall |
| Material Document And Classification: | Ams 7232 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/AN123338 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.