

**Description**

Fastener Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123352
Minimum Qty (MOQ):	80 EA
NSN:	5320-00-720-8967
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123352 Specifications

<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.154 Inches Minimum And 0.157 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Grip Length:</b>	0.021 Inches Minimum And 0.041 Inches Maximum
<b>Material:</b>	Nickel Alloy 600 Overall
<b>Material Document And Classification:</b>	Ams 7232 Assn Std Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123352> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.