

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123367
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-207-0111
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N AN123367 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Hardness Rating:	151.0 Vickers Or Firth Diamond Pyramid Maximum Overall
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123367> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.