

## **P/N AN123399**

### **Description**

Fastener Length: 11/32

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN123399

Minimum Qty (MOQ): 100

NSN: 5320-00-928-9972

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123399 Specifications**

| Fastener Length:                      | 0.334 Inches Minimum And 0.354 Inches Maximum      |
|---------------------------------------|--|
| Head Style:                           | Universal  |
| Head Height:                          | 0.054 Inches Minimum And 0.064 Inches Maximum      |
| Shank Diameter:                       | 0.123 Inches Minimum And 0.126 Inches Maximum      |
| Shank Style:                          | Straight   |
| Head Major Diameter:                  | 0.238 Inches Minimum And 0.262 Inches Maximum      |
| Grip Length:                          | 0.109 Inches Minimum And 0.129 Inches Maximum      |
| Material:                             | Nickel Alloy 600 Overall                           |
| Material Document And Classification: | Ams 7232 Assn Std Single Material Response Overall |

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123399">https://military-fasteners.com/rivets/solid+rivets/AN123399</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.