

## P/N AN123401

## **Description**

Fastener Length: 15/32",

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: AN123401

Minimum Qty (MOQ): 100

NSN: 5320-00-480-8537

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123401 Specifications**

Fastener Length:	0.459 Inches Minimum And 0.479 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123401">https://military-fasteners.com/rivets/solid+rivets/AN123401</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123401">https://military-fasteners.com/rivets/solid+rivets/AN123401</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123401">https://military-fasteners.com/rivets/solid+rivets/AN123401</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/AN123401">https://military-fasteners.com/rivets/solid+rivets/AN123401</a> and selecting the quantity you want then click "add to cart".