

## Description

Fastener Length: 9/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |  |
|-------------------------|--|
| SKU / Model:            | AN123440   |
| Minimum Qty (MOQ):      | 50   |
| NSN:                    | 5320-01-336-7623                                 |
| Schedule B:             | 7508.90.5000                                     |
| ECCN:                   | EAR99  |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



\* See page 2 for technical characteristics



# P/N AN123440 Specifications

|  |  |
|--|--|
| Fastener Length:                               | 0.281 Inches Nominal                               |
| Head Style:                                    | Universal  |
| Head Height:                                   | 0.067 Inches Minimum And 0.077 Inches Maximum      |
| Shank Diameter:                                | 0.154 Inches Minimum And 0.157 Inches Maximum      |
| Shank Style:                                   | Straight   |
| Head Major Diameter:                           | 0.296 Inches Minimum And 0.328 Inches Maximum      |
| Heat Treatment:                                | Annealed Overall                                   |
| Material:                                      | Nickel Alloy 600 Overall                           |
| Material Document And Classification:          | Ams 5687 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Passivate Overall                                  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123440> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.