

Description

Fastener Length: 13/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN123442 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-137-3759 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N AN123442 Specifications

| | |
|---------------------------------------|--|
| Fastener Length: | 0.396 Inches Minimum And 0.416 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.154 Inches Minimum And 0.157 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Heat Treatment: | As Fabricated Overall |
| Material: | Steel Comp 347 Overall |
| Material Document And Classification: | Ams 7229 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123442> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.