

Description

Fastener Length: 17/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123444
Minimum Qty (MOQ):	50
NSN:	5320-01-069-0549
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AN123444 Specifications

Fastener Length:	0.531 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.154 Inches Minimum And 0.157 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Hardness Rating:	151.0 Vickers Or Firth Diamond Pyramid Maximum Overall
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123444> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.