

Description

Fastener Length: 7/16", roughly 1050 pieces per pound, AN1234 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN123472 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-579-8110 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N AN123472 Specifications

| | |
|--|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.095 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.164 Inches Minimum And 0.172 Inches Maximum |
| Grip Length: | 0.259 Inches Minimum And 0.279 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Steel Comp 347 Overall |
| Material Document And Classification: | Ams 7229 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123472> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.