

Description

Fastener Length: 1/2", AN1234 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN123473
Minimum Qty (MOQ):	100
NSN:	5320-00-958-1438
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AN123473 Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.164 Inches Minimum And 0.172 Inches Maximum
Grip Length:	0.321 Inches Minimum And 0.341 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Steel Comp 347 Overall
Material Document And Classification:	Ams 7229 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123473> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.