

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123475
Minimum Qty (MOQ):	50
NSN:	5320-00-969-6758
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123475 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.095 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.164 Inches Minimum And 0.172 Inches Maximum
<b>Grip Length:</b>	0.446 Inches Minimum And 0.466 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Steel Comp 347 Overall
<b>Material Document And Classification:</b>	Ams 7229 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123475> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.