

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN123479                                    |
| Minimum Qty (MOQ):      | 115 EA                                      |
| NSN:                    | 5320-01-009-7233                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123479 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.209 Inches Minimum And 0.229 Inches Maximum                                  |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                       | 0.093 Inches Minimum And 0.095 Inches Maximum                                  |
| <b>Shank Style:</b>                          | Straight   |
| <b>Head Major Diameter:</b>                  | 0.164 Inches Minimum And 0.172 Inches Maximum                                  |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal  |
| <b>Material:</b>                             | Steel Comp 347 Overall   |
| <b>Material Document And Classification:</b> | Ams 7229 Assn Std Single Material Response Overall                             |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123479> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.