

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN123487 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5320-00-264-3219 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123487 Specifications

| | |
|--|--|
| Fastener Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.123 Inches Minimum And 0.126 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.210 Inches Minimum And 0.218 Inches Maximum |
| Grip Length: | 0.140 Inches Minimum And 0.160 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 7228 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123487> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.