

**Description**


Fastener Length: 3/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN123618
Minimum Qty (MOQ):	100
NSN:	5320-00-297-2886
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N AN123618 Specifications

<b>Fastener Length:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.095 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.164 Inches Minimum And 0.172 Inches Maximum
<b>Grip Length:</b>	0.009 Inches Minimum And 0.029 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123618> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.