

Description

AN123630 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123630
Minimum Qty (MOQ):	100
NSN:	5320-01-131-2292
Schedule B:	7508.90.0000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123630 Specifications

Fastener Length:	0.281 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.172 Inches Maximum
Hardness Rating:	151.0 Vickers Or Firth Diamond Pyramid Maximum Overall
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Solution Heat Treated Overall
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123630> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.