

Description

Fastener Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123636
Minimum Qty (MOQ):	50
NSN:	5320-00-205-7731
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123636 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.210 Inches Minimum And 0.218 Inches Maximum
Grip Length:	0.077 Inches Minimum And 0.097 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123636> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.